

Jailux
LIGHT EVOLUTION



We support





About Us

Established in the year 2012, at Delhi (India), we "Jai International" are highly recognized **Importer, Manufacturer and Trader of LED Light and its Fixtures**. Apart from this, the offered products are manufactured using the finest grade raw materials and sophisticated technology by our vendors. These are widely praised among clients for their quality designing, reliability, excellent performance, optimum finish and low power consumption. Moreover, these can also be availed by clients from us in various specifications as per the varied requirements of clients. In addition to this, our valuable clients can avail the offered products from us at very competitive prices.

We also make sure that before delivering our products are carefully examined by our quality controllers so that no error or discrepancy occurs at clients end. Further, our products are designed with high precision in order to meet the international quality standards. In addition to this, our ethical business practices and quality centric approach has made us one of the important names in the national market. Due to our huge designing unit and advanced fabrication techniques, we are capable of achieving large output to fulfill the bulk requirements of our clients according to their specifications. We have technical staff, researchers and sales executives who have been employed by us only after analyzing their experience and knowledge in the concerned domain.

Being a client-centric organization, we believe in attaining the highest level of contentment of our customers by offering superior quality products. We practice ethical business plans and maintain transparency in our dealings, which has enabled us in carving vast client base across the globe. Because of world-class range of products, our well-established organization has earned great appreciation from the clients. Apart from this, at our well-installed testing unit, all our products are examined stringently right from the use of raw material to their final dispatch to the customer end. We have hired an experienced quality controller that enables us to offer these products in accordance with the international standards.

Why Us?

Our vast industry experience and domain expertise have helped us in carving a niche in the domain for the company. Apart from this, our vast range of LED Lights and Led fixtures that fulfill the varied requirements of the clients helped us a lot to cater a long list of customers and becoming the preferred choices of the customers.

Some reasons that make us the obvious choice for our customers:

Quality range of products

Extensive range of products

Available at industry leading prices

LED PANEL LIGHTS (RECESS)



TECHNICAL SPECIFICATIONS

POWER	3W-24W
LUMEN	90LM/WATT
BEAM ANGLE	120-180
INPUT	90V-300VAC
LED LIFE	40000HRS
IP RATING	IP20
MATERIAL	ALUMINIUM
SURGE	2.5KVA
CRI	>80
COLOR	2700K,4000K, 6500K



LED RIMLESS PANEL



TECHNICAL SPECIFICATIONS

POWER	8W/16W/22W
LUMEN	100 LM/WATT
BEAM ANGLE	120-180
INPUT	90V-300VAC
LED LIFE	40000HRS
IP RATING	IP20
MATERIAL	ALUMINIUM
SURGE	2.5KVA
CRI	>80
COLOR	2700K, 4000K, 6500K




LED FLAT PANEL



TECHNICAL SPECIFICATIONS

POWER	20W-48W
LUMEN	90LM/WATT
BEAM ANGLE	120-180
INPUT	90V-300VAC
LED LIFE	40000HRS
IP RATING	IP20
MATERIAL	ALUMINIUM, SHEET METAL
HOUSING	1X1, 1X2, 2X2, 1X4
CRI	>80
COLOR	2700K, 4000K, 6500K



LED TUBE LIGHTS



TECHNICAL SPECIFICATIONS

POWER	8W/10W/16W/18W 22W/27W/40W/50W
PF	>0.90
THD	<18%
INPUT	90V-300VAC
LENGTH	300MM/600MM/1200MM
IP RATING	IP20
MATERIAL	ALUMINIUM, PC
HOUSING	RETROFIT, WALLMOUNTED
CRI	>80
COLOR	2700K, 4000K, 6500K RED, GREEN, BLUE



LED 2G11 LAMP & G24 LAMP



TECHNICAL SPECIFICATIONS

POWER	9W/18W/22W
BEAM ANGLE	180
INPUT	90V-300VAC
IP RATING	IP20
SURGE PROTECTION	3.5 KV
HOUSING	ALUMINIUM
CRI	>80
COLOR	3000K,6500K
LUMEN	100 LM/WATT



LED ECO BULB & T BULB



TECHNICAL SPECIFICATIONS

POWER	4W-150W
BULB BASE	B22, E27, G24
INPUT	120V-280VAC
LIGHT ANGLE	180
IP RATING	IP20
MATERIAL	PBT, PC
HOUSING	PLASTIC, FR
CRI	>80
COLOR	2700K, 4000K, 6500K RED, GREEN, BLUE



LED PREMIUM BULB

Jailux
LIGHT EVOLUTION

TECHNICAL SPECIFICATIONS

POWER	3W-15W
BULB BASE	B22, E27, E14, G24
INPUT	120V-280VAC
LIGHT ANGLE	270
IP RATING	IP20
MATERIAL	ALUMINIUM, PBT, PC
HOUSING	ALUMINIUM, THERMO PLASTIC
CRI	>80
COLOR	2700K,6500K




www.jailux.in

LED HEAVYDUTY BULB



TECHNICAL SPECIFICATIONS

POWER	3W-56W
BULB BASE	B22, E27, E14, G24
INPUT	90V-300VAC
LIGHT ANGLE	180
IP RATING	IP20
MATERIAL	ALUMINIUM
HOUSING	ALUMINIUM, PC
CRI	>80
COLOR	3000K,6500K



LED CORN LAMP

Jailux
LIGHT EVOLUTION

TECHNICAL SPECIFICATIONS

POWER	3W/5W/7W
BEAM ANGLE	360
INPUT	90V-300VAC
IP RATING	IP20
SURGE PROTECTION	2.5 KV
HOUSING	PBT
BASE	E27, B22, G24
COLOR	3000K, 6500K
LUMEN	100 LM/WATT



www.jailux.in

LED CANDLE LIGHT

Jailux
LIGHT EVOLUTION

TECHNICAL SPECIFICATIONS

POWER	3W/6W
BULB BASE	B22, E27, E14, G24
INPUT	120V-300VAC
LIGHT ANGLE	180-230
IP RATING	IP20
MATERIAL	PBT, PC
HOUSING	THERMO PLASTIC
CRI	>80
COLOR	2700K, 4000K, 6500K RED, GREEN, BLUE



www.jailux.in

LED CONCEALED DOWNLIGHT

Jailux
LIGHT EVOLUTION

TECHNICAL SPECIFICATIONS

POWER	7W-12W
BEAM ANGLE	120 - 150
INPUT	90V-300VAC
IP RATING	IP20
MATERIAL	P.C. + ALUMINIUM
CRI	>80
COLOR	3000K,6500K
LUMEN	100 LM/WATT



www.jailux.in

LED COB LIGHT SERIES



TECHNICAL SPECIFICATIONS

POWER	1W-50W
LUMEN	100 LM/WATT
BEAM ANGLE	120-180
INPUT	90V-280VAC
LED LIFE	40000HRS
IP RATING	IP20
MATERIAL	ALUMINIUM
SURGE	2.5KVA
CRI	>80
COLOR	2700K,4000K, 6500K



LED TRACK LIGHT & SURFACE COB



TECHNICAL SPECIFICATIONS

POWER	6W-50W
BEAM ANGLE	130 -150
INPUT	90V-300VAC
IP RATING	IP20
SURGE PROTECTION	2.5 KV
HOUSING	ALUMINIUM DIE CAST
CRI	>80
COLOR	3000K,6500K
LUMEN	100 LM/WATT



LED SPIKE & READING LIGHT



TECHNICAL SPECIFICATIONS

POWER	5W/9W/12W
BEAM ANGLE	130
INPUT	90V-300VAC
IP RATING	IP65
SURGE PROTECTION	2.5 KV
HOUSING	ALUMINIUM DIE CAST
CRI	>80
COLOR	3000K,6500K
LUMEN	100 LM/WATT



LED BOLLARD LIGHT



TECHNICAL SPECIFICATIONS

POWER	12W/18W
INPUT	90V-300VAC
IP RATING	IP65
SURGE PROTECTION	2.5 KV
HOUSING	STAINLESS STEEL
CRI	>80
COLOR	3000K,6500K
LUMEN	100 LM/WATT




LED UNDERGROUND LIGHT



TECHNICAL SPECIFICATIONS

POWER	1W/3W/5W
BEAM ANGLE	120
INPUT	90V-300VAC
IP RATING	IP65
SURGE PROTECTION	2.5 KV
HOUSING	S.S + P.C
CRI	>80
COLOR	3000K,6500K
LUMEN	100 LM/WATT




LED FOOT LIGHT



TECHNICAL SPECIFICATIONS

POWER	3W/6W
BEAM ANGLE	100
INPUT	90V-300VAC
IP RATING	IP20/IP65
SURGE PROTECTION	2.5 KV
HOUSING	ALUMINIUM DIE CAST
CRI	>80
COLOR	3000K,6500K
LUMEN	90 LM/WATT



LED STRIP



TECHNICAL SPECIFICATIONS

POWER RANGE/MTR	4.8,9,14.4
BEAM ANGLE	180
INPUT	12V & 220V
IP RATING	IP20, IP65
COLOR	Single (Warm White, Blue, Red, White, Green) and RGB (Red, Green, Blue)
LENGTH RANGE	FOR 12V: 5 MTR FOR 220V: 50/100 MTR


5050 SMD



3014 SMD



2835 SMD



LED PROFILE LIGHT



TECHNICAL SPECIFICATIONS

LENGTH	1 MTR-3MTR
INPUT	12V
IP RATING	IP20
HOUSING	ALUMINIUM DIE CAST
CRI	>80
COLOR	3000K,6500K (RED,GREEN, BLUE)




LED HIGHBAY LIGHT

Jailux
LIGHT EVOLUTION

TECHNICAL SPECIFICATIONS

POWER	25W-200W
BASE	B22, E27, HANGING
INPUT	90V-300VAC
LIGHT ANGLE	160
IP RATING	IP20
MATERIAL	ALUMINIUM
HOUSING	ALUMINIUM, PC
CRI	>80
COLOR	3000K,6500K
LUMEN	130 LM/WATT



www.jailux.in

LED FLOOD LIGHT & STREET LIGHT



TECHNICAL SPECIFICATIONS

POWER	30W-250W
INPUT	90V-300VAC
LIGHT ANGLE	150
IP RATING	IP65-IP67
MATERIAL	ALUMINIUM
HOUSING	ALUMINIUM DIE CAST
CRI	>80
COLOR	3000K,6500K
LUMEN	130 LM/WATT



LED FLAME PROOF LIGHT (WELL GLASS FITTING)

Jailux
LIGHT EVOLUTION

TECHNICAL SPECIFICATIONS

POWER	40W/50W
BEAM ANGLE	140-180
INPUT	90V-300VAC
IP RATING	IP67
SURGE PROTECTION	10 KV
HOUSING	ALUMINIUM DIE CAST
CRI	>80
COLOR	6500K
LUMEN	100 LM/WATT




www.jailux.in

LED SOLAR PRODUCTS



TECHNICAL SPECIFICATIONS

POWER	3W-36W
BEAM ANGLE	140-160
INPUT	12V-220VAC
IP RATING	IP20/IP65
BATTERY	INCLUDED
HOUSING	PC, ALUMINIUM
CRI	>80
COLOR	3000K,6500K
LUMEN	100 LM/WATT





LED TUBE HOUSING & SKD



TECHNICAL SPECIFICATIONS

POWER	18W/22W/27W/40W/52W
PCB	MCPCB
DRIVER INPUT	90V-300VAC
SMD	2835
SURGE PROTECTION	3.5 KV
HOUSING	ALUMINIUM, PC
CRI	>80
COLOR	3000K,6500K



CUT-OUT CHART



Sl. No.	Product	Wattage	Size (mm)	Cut-out (mm)
1	LED Panel Light (Recess Round)	3W	90	80
		6W	120	110
		9W	150	138
		12W	172	162
		15W	192	180
		18W	225	215
2	LED Panel Light (Recess Square)	3W	90x90	80x80
		6W	120x120	110x110
		9W	150x150	138x138
		12W	172x172	162x162
		15W	192x192	180x180
		18W	225x225	215x215
3	LED Flat Panel Light (Square)	36W	600x600	595x595
		40W	600x600	595x595
		48W	600x600	595x595
4	LED COB Down Light (Round)	3W	65	55
		6W	90	75
		9W	90	75
		16W	115	100
		24W	135	120
		30W	160	135
5	LED Rimless Panel Light (Round)	8W	90	75
		15W	140	122
		22W	165	145



Authorised Distributor

JAI INTERNATIONAL

Head Office: 290, Vikas Kunj, Vikas Puri, New Delhi- 110018. India.
Factory Address: Plot No. A-86, Keshopur Industrial Area, Vikas Puri, New Delhi - 110018